

Access Link

POINT-TO-PAIR-3

UConnect All Ears Soundfield and Voice Save Solutions



New Flexmike is
28% smaller & 33% lighter



A wireless microphone for
the teacher, a wireless audio
platform for the future.

Access Link lets you add wireless microphones to
virtually any amplifier and speaker system, allowing
freedom of motion and ensuring all students hear
every spoken word.

With equal access to instruction, research has
proven students are more attentive and on-task
while redirections are dramatically reduced.

Access Link can also add a student
pass-around microphone and up to 12 tap-to-talk
(T3) student microphones to ensure all students can
be clearly heard by their peers.



SHAREMIKE



FLEXMIKE

Add microphones and media to existing audio

Add microphones to your existing system



Clearer instruction and more student participation

With Access Link connected to your existing audio amplifier and speakers, the Lightspeed Flexmike microphone projects the teacher's voice through your audio system so every child hears the instruction.

With a second microphone for pass-around use, students take the stage and share with their peers.

Add Tap-to-talk student microphones



Build an environment of sharing and communication

Access Link can bring as many as 12 tap-to-talk (T3) student microphones to any classroom audio system.

T3 microphones allow students to simply tap a button and begin speaking into their microphone, ensuring they are clearly heard by their peers.

Easily expand for media and small groups



Add 2-way interactive audio and wireless media integration

Access Link provides scalability as instructional methods evolve. For small group learning, it works seamlessly with Activate pods for student monitoring and assessment.

Use the Activate Station with Bluetooth to connect to mobile devices for control and audio streaming.

Specifications

Description	Wireless microphone system
Wireless Communication	Access Technology (1.9 GHz)
Wireless Transmission Range	Up to 200 ft. (60m) open field
Audio Output Level (Nominal)	Line Mode: 316 mV RMS (2V RMS max) Mic Mode: -40 dB of line mode
Frequency Response	120 Hz - 8 kHz
Total Harmonic Distortion (THD)	<1% @ 10W
DC Power Input	5V/250mA USB-C connector
Audio Input (with volume control)	One (1) Input (3.5 mm)
Audio Outputs	3.5mm unbalanced; 3-pin euro-block balanced
Tone Control	Bass / Treble
Warranty	5 Years
Dimensions (W x D x H)	7.6" x 5" x 1.13" (193 x 127 x 29mm)
Weight	9.5 oz (269g)

Access Link™

POWERED BY ACCESS TECHNOLOGY



FRONT



BACK

Microphone & Charger

SHAREMIKE AND FLEXMIKE
FOR STUDENTS AND TEACHER

